





Document Solutions

> PRINT > COPY > SCAN > FAX

TASKalfa 1801
TASKalfa 2201

MONOCHROME
MULTIFUNCTION PRODUCT
FOR A4/A3 FORMAT

COMPACT AND TOUGH A MARK OF TOP RELIABILITY



The TASKalfa 1801 and TASKalfa 2201 is highly flexible multifunctional device for all documents up to A3. Fast warm-up and print, and copy speed of up to 22 pages per minute in A4 speaks for themselves. While the optional duplex unit saves resources, the additional paper cassettes ensure that even larger jobs can be handled easily. Together with its compact design, and user-friendly operation, it is the right choice for any busy team.

- > Copy, Print, Color Scan as standard and Fax* optional
- > Fast first copy/print time in just 5.7 seconds
- > Support LAN expandability for network print and scan**
- > Standard 256MB memory
- > Standard 300 sheets paper cassette and 100 sheets multi-purpose tray with maximum paper capacity up to 1,300 sheets
- > Environmental friendly design with up to 150,000 pages long life drum unit and duplex printing capabilities***

*Optional Fax System(X) required **Optional IB-33 Network Interface required ***Optional Duplex Unit DU-480 required



| Main Specifications | | |
|--|---|---|
| Model | TASKalfa 1801 | TASKalfa 2201 |
| Main Function | Copy, Print, Scan, Fax (Optional) | |
| Writing Method | Semiconductor Laser | |
| CPU | 500MHz | |
| Print Speed (A4) | 18 / 11 cpm | 22 / 11 cpm |
| Memory | Standard 256MB (maximum) | |
| Warm Up Time | 17.2 seconds | |
| Paper Capacity | Standard | 400 sheets : 1 x 300 sheets (Cassette) + 100 sheets (MPT) |
| | Maximum | 1,300 sheets (Main Unit + PF-480 x 3 + MPT) |
| Paper Size | Cassette | Min. A5R - Max. A3 (Ledger) |
| | MPT | Min. A6R - Max. A3 (Ledger) |
| Paper Weight | Cassette | 64 to 105 g/m ² |
| | MPT | 45 to 160 g/m ² |
| Duplex Printing (Optional) | Paper size : A5R to A3; Paper weight : 64 to 105 g/m ² | |
| Display LCD (Back Light) | 5-line, 128 x 64 dot | |
| Dimension (W x D x H) (Main Unit) | 565 mm x 527 mm x 485 mm (with platen cover) | |
| Weight (Main Unit) | 27kg (with platen cover) | |
| Power Source | AC 220 ~ 240 V, 50/60 Hz | |
| Power Consumption (Standard configuration) (220 to 240V) | Copy/Print Mode | 385W or less |
| | Stand-by Mode | 75W or less |
| | Energy Saver | 1.54W or less |
| Noise (ISO7779/ISO9296) | Copy/Print Mode | 62dB(A) |
| | Stand-by Mode | 40dB(A) |
| Safety Standards: GS, TUV, CE | This unit is manufactured according to ISO 9001 standard and ISO 14001 environmental standard. | |
| Copy Functions (Standard) | | |
| Copy Size | Max. A3 (Ledger) - Min. A6R | |
| Resolution | 600 x 600 dpi | |
| First Copy Time | 5.7 seconds | |
| Zoom Ratio | Manual | 25% to 400% (1% per Step) |
| | Pre-defined | 5R5E |
| Multiple Copy | 1 to 999 | |
| Features | ID Card Copy, N-up layout mode (2-in-1, 4-in-1), ECOprint mode, Rotated Copy, Rotate Sort, Interrupt Copy, Department Accounting : 30 | |
| Print Functions (Standard) | | |
| Resolution | Fast 1200 | |
| PDL | Host Based (GDI) | |
| Connectivity | Plug & Play (USB), SNMP | |
| Operating System Supported | Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows XP, Windows Vista, Windows 7, Windows 8; Apple Macintosh OS 10.5 or more, Linux OS | |
| Interface | USB2.0 High Speed x1; 100BASE-TX/10BASE - TX | |
| Network Printing (Optional) | Port 9100, LPR : IB-33 | |
| Print Box | Registration : 30 with password setting | |
| Scan Functions (Standard) | | |
| Color Selection | Full Color; Grayscale; Mono | |
| Resolution | Color: 300dpi, 200dpi; Mono: 600dpi, 400dpi, 300dpi, 200dpi | |
| File Format | TIFF (MMR/JPEG compression), PDF (MMR/JPEG compression/High Compression PDF), JPEG, BMP | |
| Image Type Mode | Text, Photo, Text + Photo | |
| Transmission Type | Scan to PC (SMB); Scan to E-mail; TWAIN Scan; WIA Scan, Scan Utility: Client Tool | |
| Address Storage | 30 addresses | |
| Fax Functions (Optional) | | |
| Original Size | Max. A3 (Ledger) – Min. A5 (Statement) | |
| Coding Method | MMR, MR, MH | |
| Transmission Speed | Super G3 33.6 kbps | |
| Transmission Time | 4 seconds or less (MMR) | |
| Fax Resolution | Normal, Fine, Super Fine | |
| Memory | Standard: 4MB | |
| Network FAX | Yes (Transmission Only) | |
| One Touch Dial | 32 | |
| Consumables | | |
| Toner Kit | TK-4109 : 15,000 pages with 5% coverage; Average starter toner : 3,000 pages with 5% coverage | |
| Maintenance Kit | MK-4105 : 150,000 pages with 5% coverage | |
| Options | | |
| Platen Cover | Platen Cover Type H | |
| Document Processor | DP-480 : 50 sheets RADF | |
| Paper Feeder | PF-480 : 300 sheets x 1 Paper Feeder, A4 / Letter (max. 3 x PF-480 can be added to the basis-system) | |
| Duplex Unit | DU-480 : 64 - 105g/m ² , A3 - A5R | |
| Network Card | IB-33 : 100BASE - TX/10BASE - TX | |
| Fax System | Fax System(X) | |



KYOCERA Document Solutions Singapore Pte. Ltd.
 12 Tai Seng Street #04-01A Luxasia Building Singapore 534118
 Tel : (65) 6741 8733 Fax: (65) 6748 3788
www.KyoceraDocumentSolutions.com.sg

*KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

@All rights reserved. Brochure/KDAS/201308/KIZUNA

KYOCERA Business Partner



Scan for more information



www.KyoceraDocumentSolutions.com.sg